

# Verificador de Precios RH

## Smart Checker Terminal



1. Shops can install the smart checker in every aisle or department as the terminal is compact, easy-toinstall and with affordable cost.
2. Apart from checking the price of the items customers want to buy, they can also check the product details (like the country of origin, usage and ingredient ... ) and also look up the balance of their gift cards, loyalty point balance.
3. Customers can also simplify call for assistance with a simply touch on the screen.
4. Our smart checkers can also be connected to any mobile printers, allowing retailers to build on the solution which can allow more valuable and complicated services.
5. For example, customers can print out recipes, gift registries and coupons for in-store specials as well as their own coupons based on their loyalty cards they scanned.
6. More, the smart checker can also be used to show some advertisements so that the shops can charge the air time from the merchandisers for showing the advertising videos / pictures of their products.
7. The shops can also upsell / cross-sell the customers other products which are related to the items being scanned.
8. The traditional price checkers maybe the burdens for the shops while our smart checkers can act as the active shop sales assistants, bringing more revenue to the shops.



### SPECIFICATION

<b>Motherboard</b>	ARM-Linux / Android	Intel-Windows
<b>CPU</b>	RK3288 CPU Cortex A-17 Quad-Core	J1900 CPU
<b>Memory &amp; Storage</b>	2GB DDR3; 16GB eMMC	4GB DDR3; 120GB SSD
<b>Interfaces</b>	1 x DB9-RS232; 2 x USB type A; 1 x RJ45-LAN	
<b>TFT Display and Touch</b>		
<b>Active Screen Area</b>	216.96x135.6 mm	
<b>Resolution</b>	1280x800, support 16.7M color	
<b>Dot pitch</b>	0.0565 × 0.1695 mm	
<b>Brightness</b>	350 cd/m2	
<b>Touch</b>	PCAP touch, support 10 multiple touch//ELO-5 wire resistive	
<b>Scanner Features</b>		
<b>Illumination</b>	White LED 2700K, Aiming: Green LED, 525nm	
<b>Field of View</b>	Horizontal:38°,Vertical:48°	
<b>Scanning Angles</b>	±58,±65°,360°(skew, pitch, roll)	
<b>Barcodes supported</b>	1D - UPC-A,UPC-E,UPC-E1,EAN-13,EAN-8,ISBN/ISSN,Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar(NW7), Code 128, ISBT 128, COde 93, Code 11(USD-8), MSI/Plessey, UK/Plessey,UCC/EAN 128(GS1-128), China Post, China Finance, GS1 DataBar 2D - PDF417, QR code, DotMatrix, Han Xin Code, Aztec COde, GS1 Composite	
<b>Others</b>		
<b>Power Adaptor</b>	Powered by 12V 2A	
<b>Network</b>	10/100/1000Mbps	
<b>Wireless</b>	802.11b/g/n (optional)	
<b>Storage Temperature</b>	-20oC to 60 oC	
<b>Storage humidity</b>	0 to 100%	
<b>Working Temperature</b>	0 oC to 50 oC	
<b>Working humidity</b>	10% to 90%	